

Viblock Wet Look Sealer is a durable, multi-purpose sealer that can be applied to internal and external concrete floors. Viblock Wet Look Sealer protects the concrete from staining and marking, making it easy to clean and maintain. Designed for application in high use areas, Viblock Wet Look Sealer can withstand vehicular traffic, making it perfect for driveways and garages. Viblock Wet Look Sealer is quick drying and easy to apply.

Precautions:

- Viblock Wet Look Sealer contains flammable solvents - read 'Safety and Handling' information (over page) prior to application.
- Concrete must be fully cured prior to application i.e. *at least* 4 weeks old.
- Viblock Wet Look Sealer cannot be applied to any surface that has been previously coated with any other surface treatment.
- Viblock Wet Look Sealer cannot be applied to concrete below 10°C or above 30°C.
- Viblock Wet Look Sealer should not be applied in the hottest part of the day, or if rain is likely within 8 hours of application.
- Viblock Wet Look Sealer will not act as a filler - pitting or pinholes in the concrete may result in spotting or 'measling' of Viblock Wet Look Sealer when the concrete is wet.

Preparation:

The concrete surface must be properly prepared to enable optimal performance of Viblock Wet Look Sealer. The surface should be clean of any marks or stains as they may prevent sealer adhesion to the surface, or become entrapped by the sealer.

- **New Concrete:** New concrete should be allowed to cure (at least 4 weeks) prior to application. Surface should be then given an acid etch to remove efflorescence (surface latence), ensuring all residue is completely removed (washed away).
- **Existing concrete:** Care must be taken to prepare the surface correctly:
 - Remove ALL existing coatings: Sealer must be applied directly to concrete surface.
 - Remove ALL contaminants: All stains and marks should be removed using the appropriate cleaning agents. If area is heavily contaminated, it is recommended that Wet Look Sealer is NOT applied as there is an increased chance of delamination.

Test Area: It is recommended that Wet Look Sealer is applied to a test area prior to application over the entire surface to ensure that the sealer correctly adheres and gives the desired look and finish.

Application:

Viblock Wet Look Sealer can be applied with roller, broom or sprayer.

- A roller is recommended for smooth surfaces (i.e. internal floors) while brooming or spraying is recommended for external or textured surfaces.
- Ensure sprayer is equipped with solvent resistant seals.

Apply in thin coats, avoid pooling

Apply *minimum* of 2 coats

- Porous and ground surfaces will require additional coats to be properly sealed.
- Do not apply further coats until previous coat is completely dry.

Application continued over page...

Application continued...

- Drying time: Viblock Wet Look Sealer typically dries within 2-4 hours of application.
- This period may be longer in cold climates, and varies depending on atmospheric conditions, the condition of the prepared surface, and application.
- Coverage: First coat: Approximately 5-6 m²/L
Second (and subsequent coats): Approximately 6-8 m²/L
- Coverage will vary greatly depending on the concrete porosity and texture.
- Cleanup: All equipment can be cleaned xylene-based thinners.
- Maintenance: Once sealed, the concrete surface should be cleaned with non-amonia based cleaners.
- Removal: Wet Look Sealer can only be removed by mechanical (i.e. grinding).

Safety and Handling:

- Hazard: Viblock Wet Look Sealer is a Class 3A hazard.
UN Number: 1263 DG Number: 3b
Poison Schedule: 5 Hazchem code: 3(Y)E
- Safety: Wear suitable protective clothing, eye protection, protective gloves, and respirator.
- Storage: Store in cool, dry, well ventilated place in original container. Store out of reach of children. Store away from direct sunlight, oxidizing agents (e.g. nitrates), acids, anionic, detergents, and foodstuffs. Keep away from naked flames and other heat sources. Take precautions against static discharge. Ensure container is sealed when not in use, and checked regularly for leaks or spills. Do not allow vapours to collect in enclosed spaces. Wet Look Sealer (solvent based) can be stored for up to 12 months.

First Aid:

- Swallowed: DO NOT induce vomiting. Give water or milk to drink. Obtain medical attention immediately. For emergency information contact the National Poisons Centre (0800 764 766).
- Eyes: Immediately flood with copious quantities of water, holding eye open if necessary, for at least 15 minutes. Seek urgent medical attention.
- Skin: Remove contaminated clothing and shoes and wash skin thoroughly with excess water. If irritation occurs or persists, seek medical attention. Launder clothing and clean shoes before re-use.
- Inhalation: Remove patient from exposure, keep warm and at rest. If there is respiratory distress, give oxygen and seek immediate medical attention.

Properties:

Appearance..... colourless liquid
Appearance when dry..... transparent ('Wet Look' to gloss finish)
Odour..... aromatic/solvent odour
Solubility..... insoluble
Flash Point..... 24°C
Vapour Pressure..... 1000 mm Hg @ 20°C
Wet film thickness..... typically 75 - 100 micron
Dry film thickness..... typically 20 - 30 micron

Product Warranty: The information contained in this document is true and accurate to the best knowledge of Allied Concrete. We cannot however anticipate all conditions under which this information and our products may be used. Viblock therefore accepts no responsibility and offers no warranty with respect to results obtained by the application of our products, their suitability, or for their safe use. Viblock warrants our products to be free of manufacturing defects. If the product when purchased was defective and was within recommended storage life when used, Viblock will replace the defective product with new product without charge to the purchaser. Viblock makes NO OTHER WARRANTY, either expressed or implied, concerning our products.